

ALLFLEXDOT 4131A

safety work gloves

The Safety Jogger ALLFLEXDOT work gloves are perfect for any demanding industry. Offering durability, flexibility and superior protection, they are a reliable choice for any worker.

Performance level	4131A
Liner	15 GAUGE NYLON
Coating	FOAM NITRILE / NITRILE DOTS
Category	TSF-Touchscreen function
Size range	EU 7-11
Sample weight	0.047 kg
Norms	EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry, Tactical



BLK

Performance level 4131A

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- Tear resistance: based on the amount of force required to tear the sample.
- Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.